

60kg Electric magnetic lock

Features:

Collinear Load Test 60kg,120pounds

Dual Voltage 12 or 24 VDC(optional)

The Standard Voltage is 12VDC when Finished

MOV Provides Reverse Current Protection

Anti-Residual Magneism Designed

High Strength Material,Anodized Aluminum Housing

Design with no Mechanical Bolt

Increase the holding Force,Dual Insulative Hosing

Application: File Cabinet ,Display Cabinet

Product Parameter:Parameter Spec.

| | |
|-----------------------|---------------------------------------------------------|
| Place of Origin | Guangdong, China (Mainland) |
| Brand Name | Proyu |
| Model Number | PY-EL5-1 |
| Type | Mini 60kg electromagneitc lock |
| Lock size | 80Lx35Wx20H(mm) |
| Armature plate size | 180 x 38 x 11mm |
| L type bracket | L80xW40xH3 |
| Holding force | 60kg(120Lbs) |
| Dual voltage | 12/24VDC+10% |
| Current | 12V/300mA 24V/150mA |
| Suitable for | File Cabinet ,Display Cabinet |
| Surface Temp | $\leq +20^{\circ}\text{C}$ |
| Operating Temp | 10~+55°C(14-131F) |
| Suitable for | wooden doors, glass doors, metal doors, fireproof doors |
| Suitable Humidity | 0~90%(non-condensing) |
| Finishes for Shell | Anodized aluminum |
| Finishes for Magnetic | Zinc |
| Finishes for Armature | Zinc |
| Weight | 0.5kg |



