

RFID

PY-V806MJID1101

PROYU equipment.It relatives.In

□□

- 7" TFT LCD
- LED
- 16
- 14
- 2
- 4

□□□□

□□ □□	
□□	7" □ □ TFT LCD □ 16□9□ □□
□□□	480 * RGB * 234
□□ □□	AC100V-240V □50Hz-60Hz□
□□ □□	DC 15V
□□ □□	1200mAh□
□□ □□ □□	120□ ±10□
□□ □□ □□	40□□ ±10□
□□ □□	80M □4x0.65 □□□□□
□□ □□	□□□ 0.5W; □□□ 8W
□□ □□ □ □□	□□ 200□
□□ □	65°
□□□ □□	AC100□ 240V□ 50 / 60Hz□
□□□ □□	DC 15V
□□ □□	-40°C□+ 70°C
□□ □□	-20°C□+ 60°C
□□	□ □□/□□ □ □□□
□□	225□L□* 128□□□* 23□□□mm
□ □□	460□
□□ □□	
□□ □□	IR □□ □□ □ □ □
□□ □	92° □ □
□□□	> 420 □□ □
□ □□	□□
□□ □□	□□□ 0.1W; □□□ 4W
□□ □□	-10°C□+ 55°C
□□	□ □□

□□	168□L□* 110□□□* 65□□□mm
□ □□	310□