□□□□□□□□rfid□□□□PY-iface800

□□□

□□□□□	□□ □□□CPU 800 MHz
□□	256M□□□64M SDRAM
□□□□	ZEM800□□□□□□□
□□□□□	□□ □□□□□□□□□□□
□□	□□□□□□□□□
□□	4.3“TFT□□□
□□□	1200□1□N□
□□□□	2000
□□□□	100000
□□□□	□□ □□7.0& □□ □□10.0
2000mAh□□□□	□□□
□□	TCP / IP□RS232 / 485
USB-HOST	□□USB□□
□□□□	□□□
□□□□□□	□□□□□□□□□□□□□□□□□□□□□□□□□□□□□T9□□□9□□□ID□DLST
□□□□□□	□□□□□□□□□□□□□□□□
□□□□	□□
OEM	□
SDK	□□□
□□*ulti*□□	□□□
□□□	□□
□□□□□□□□	□□□
□□□□	□□□□□□IC□□□□□□□□□□□□□□□Web□□□□GPRS□WIFI
□□	12V3A
□□□□	≤2□
□□□□	0°C- 45°C

rfid□□□□

□□□□□□□□□□□□□□ □□□ □□□□□□□□□

15:55
/18
F1
F2
F3
F4
F5
F6
F7
F8
FaceID0

SN : 6250611230782

Insert This Side Up
Rechargeable Lithium-Ion Polymer Battery
Model Number : ZK-K7
Rating: 7.4V 2350mAh
Read instructions in operating guide before
Using the battery
WARNING: To reduce risk of fire or burns, do
not expose battery to temperatures exceeding 60°C
(140°F). Do not disassemble, crush, puncture,
short external contacts, or dispose of in fire or
water. Only replace with the battery pack
designated for this product.
CE

PC
PC
RS232/485
Converter
TCP/IP
HUB
RS485
Sensor
Lock
iface800
Electric Bell
Exit Button
Door
USB Key
Serial Printer