

## 60kg Electric magnetic lock

### Features:

Collinear Load Test 60kg,120pounds

Dual Voltage 12 or 24 VDC(optional)

The Standard Voltage is 12VDC when Finished

MOV Provides Reverse Current Protection

Anti-Residual Magneism Designed

High Strength Material,Anodized Aluminum Housing

Design with no Mechanical Bolt

Increase the holding Force,Dual Insulative Hosing

Application: File Cabinet ,Display Cabinet

### Product Parameter:Parameter Spec.

Place of Origin	Guangdong, China (Mainland)
Brand Name	Proyu
Model Number	PY-EL5-1
Type	Mini 60kg electromagneitc lock
Lock size	80Lx35Wx20H(mm)
Armature plate size	180 x 38 x 11mm
L type bracket	L80xW40xH3
Holding force	60kg(120Lbs)
Dual voltage	12/24VDC+10%
Current	12V/300mA 24V/150mA
Suitable for	File Cabinet ,Display Cabinet
Surface Temp	$\leq +20^{\circ}\text{C}$
Operating Temp	10~+55°C(14-131F)
Suitable for	wooden doors, glass doors, metal doors, fireproof doors
Suitable Humidity	0~90%(non-condensing)
Finishes for Shell	Anodized aluminum
Finishes for Magnetic	Zinc
Finishes for Armature	Zinc
Weight	0.5kg



