

Carte perforée fréquentation à temps de la machine PY-S880

Paramètres:

Carte Capacité	10000
Transaction Capacité	50000
Plate-forme matérielle	ZEM510
Communication	RS232 / 485, TCP / IP, USB hôte
Fonctions standard	Workcode, SMS, DLST, planifiée cloche, Self-Service Query, Switch statut automatique, saisie T9, photo-identification, Appareil photo, serveur Web
Interface de contrôle d'accès pour les	3e serrure partie électrique, capteur de porte, bouton de sortie, alarme, porte de Bell
Wiegand Signal	Entrée & amp; Sortie
Fonctions en option	ID / IC, Wi-Fi, GPRS
Exposition	3,5 pouces d'écran TFT
Source De Courant	1.5A 12V DC
Température de fonctionnement	0 °C - 45 °C
Humidité de fonctionnement	20% -80%





Packing list

For time attendance device:

In addition to the device, this package includes the following items:

- Printed documentation and software CD
- AC adapter
- Accessory package
- ID card (only for device with RFID function)

For access control device:

In addition to the device, this package includes the following items:

- Printed documentation and software CD
- Accessory package
- ID card (only for the device with RFID function)

Contents may vary depending on the device configuration.

The information contained herein is subject to change without notice.

