

PY-CR47
 125KHz
 5cm
 MIFARE®

Features

- 125KHz 125kHz 10cm (125KHz) / 5cm (MIFARE®)
- 2Wiegand 26bits (Wiegand34, RS232 26bit Wiegand 26bits 26bits 26bits)
- 125KHz 125kHz 10cm (125KHz) / 5cm (MIFARE®)
- 125KHz 125kHz 10cm (125KHz) / 5cm (MIFARE®)
- 125KHz 125kHz 10cm (125KHz) / 5cm (MIFARE®)
- 125KHz 125kHz 10cm (125KHz) / 5cm (MIFARE®)
- 125KHz 125kHz 10cm (125KHz) / 5cm (MIFARE®)
- 125KHz 125kHz 10cm (125KHz) / 5cm (MIFARE®)

Specifications

Model	125KHz	MIFARE®
Operating Frequency	125KHz 10cm	5cm
Operating Voltage (V)	≤300ms	
Operating Current (mA)	5 ~ 16V / Max.70mA	
Operating Temperature	2ea (125KHz 10cm, 5cm)	
Operating Mode	26bit Wiegand (125KHz 10cm)	Wiegand34, RS232 26bit Wiegand 26bits 26bits
Operating Time	125KHz 10cm (125KHz 10cm)	
Operating Voltage	125KHz	
Operating Temperature	-20 ~ + 65 °C	
Operating Mode	125KHz 10cm 10% 90%	
Operating Voltage	125KHz	
Operating Temperature	125KHz 10cm + 125KHz	
Operating Mode	125KHz 10cm 86 * 86 * 25	

Pin Configuration

- 125KHz 5V-16V
- GND
- 1
- D0
- 125KHz
- 125KHz
- 125KHz

