

Frameless glass doors up and down power plug lock

Features:

- * Low Temperature, safe & Durable
- * Low Power, Environmental Protection
- * Special photo electricity control,three steps current application
- * Long Life with 500000 Operations
- * MOV Provides Reverse Current Protection
- * Superior Strength Aluminium Alloy,Solid Stain-less Steel Bolt
- * Autolock Time Delay: 0,3,6,9sec.
- * Door statue signal output contact(NC.COM)
- * Double protection for loading current
- * Auto-relock if no Action within 5 secs.
- * Photoelectricity Control,Low Temperature,
A:The Low Current is Changed immediately;
B:When door frame doesn` t coincide with door leaf ,door leaf against the bolt,then the electric bolt will start the low-power function to bring low temperature.

C:The Photoelectricity Control Technology, prevent the machanical defect.

Technical Specifications:

Place of Origin	Guangdong, China (Mainland)
Brand Name	Proyu
Model Number	PY-EL8
Fail Safe	Lock when energized
Face Plate	L148xW43xH39(mm)
Bolt	17mmDIA,stainless steel 13mm throw
Voltage	DC12V(DC24V)
Start Current	900mA
Standby Current	120mA
Support Grip	400kg
Suitable For	12mm Electric Bolt For Fully Frameless Glass Door
Signal Output	Door Status Output,NO/COM
Surface Temp	Low Temperature
Induction Distance	8mm
Operating temp	-10~+55°C(14-131F)
Operating Humidity	0~90%(non-condensing)
Special Designed	Tested to 500000 operations
Face place material	Stainless Steel
Weight	1.8kg

