

00 / 0000000000 000000-00 **3-6** 00 0000 00000 00000000000 000000000000 00000000 00000

0000000000:
 0000 0000000000 0000: 0000000000000,MIFARE® 000000, 0000000000 000000, 000000 0000000000 000000 (0000000000)
 000000 00 00000000 00 000000 00 000000 00 0000 0000000000
 00000000: 120 00000000000000 00 120 0000000
 000000 00 00 0000 0000 000000 0000 0000000000 00000 00000000 00000 0000
 000000 000000 0000 0000000000 00 0000 000000000000 00000000 0000000000
 0000 00000000 00 0000 0000000000 00000000 00 0000 00000000000000 0000000 00000 00 000000 00
 0000000000 00 000000000000 000000000000 000000
 0000 3080UV 00 0000 00000000 00
 00 0000000000 00000000 (4.8 00 00 00)
 0000 000000 00 00000000 00000000 00000 00 00 000000000000 0000000 00 0000000000 00 00000000 00000 00 00000 00
 0000000000 000000 00000000 00000000, 00000000 00 & 000000 00000000 0000 000000000000 00000000, 00 0000000000 000000 0000000000
 000000

00000000 00000000:	
000	PY-U3-6
00000000 - 0000 00000000	0.300000 0000000000, 0000 CMOS
00000000 00000000	500 00000000
00000000 0000 00 00000000 0000000000	00 20 00000000000000 000000 00 00 4H 00000000 00 0000 1000 0000 0000 00000 00 0000 00000000 000000 000000
0000000000 0000	& LT; 1 00000000
0000000000 00000	1: 00
FRR	≤1%
0000	≤0.0001%
000000 00 00000000 00 0000 0000	0000 00 0000
0000000000000000000000 0000000000 000000	00 000000000000000000000000 0000000000 000000 00 0000 00 0000 00000000 00000000
000000000000000000000000 0000000000 000000	000000 0000 00 000000000000
000000000000000000000000000000000000 0000	0000 000000000000000000000000000000000000 00 000000000000 0000 00 00000000 00000000
000000000000 00000000	00000000 120 00000000000000
0000000000 0000	& lt; 20UA (0000000000000000) & lt; 120UA (00000000 0000000000) & lt; 220UA (00000000 0000000000 00 00000000 0000000000)
00000000 0000	& LT; 200mA
000000000000 0000000000	4 00 0000000000 00000000, 00000 6V
00000000 00000	0000000000 10, 000 0000
00000000 00 0000000000	4 00 0000000000 00000000 / 6V ~ 9Vexternal 00000000 00 0000000000
00000000 00000000	-10 00000000 0000000000 ~ 55 00000000 0000000000
00 0000000000 00000000	& LT; 4.5V

00000000 00000000 00:











