

PY-V806MJM11

 $1_{\square}~2.4~{\rm G}~{}_{\square\square\square\square}~{}_{\square}~{}$

20 00 000 000000-000000000 000000000, 000-00000 0000000

30 7 000 TFT 000 00000000 00000

40 000000 00000 00 000 0.3Mega 0000000

 $60\ 00000\ 000000\ 00\ 000\ 000\ 000$

110 00000-000 16 000 00 0000

960 * 480 90dBm 111 111 111 1111 250mA

_____ 20-30mA 3.7 v /

0000 00000 1350mah

□□□□□ □□□□□□ AC100 ~ 240V, 50/60 □□□□□□, DC5V/1A

החחחח הח החח 6W

-10° C ~ + 50° C

22.5 * 12.8 * 2.3 [

□□□□□□ CameraTechnical □□□□□□□:

0000 00000 1/4 000 CMOS OV7725

____: 628 * 582 NTSC:510 * 492

> 420 000

Focus(mm) 3.6 [[[[[]]]]

1350mah

□□□□□□ □□□□□ AC100 ~ 240V, 50/60 □□□□□□

000000 00000 DC5V/1A

(□) 168×(W) 110×(D) 65 □□□□

00000 000 00000 000:

- 1 * 00 00 0000 00000
- 1 * 00000 000000

- 1 * 00000 000000 00 000 000 0000000
- 2 * rechargeable [][[][]
- 1 * 000000 0000
- 1 * 000000 00 00000
- 1 * 000000000 0000000 00000000