

## Electric Bolt With Mort Lock Cylinder

### Features:

- \* Low Temperature, safe & Durable
- \* Low Power, Environmental Protection
- \* Special photoelectricity control, three steps current application
- \* Long Life with 500000 Operations
- \* MOV Provides Reverse Current Protection
- \* Superior Strength Aluminium Alloy, Solid Stainless Steel Bolt
- \* Double protection for loading current
- \* Auto-relock if no Action within 5 secs.
- \* Photoelectricity Control, Low Temperature,
  - A: The Low Current is Changed immediately;
  - B: When door frame doesn't coincide with door leaf, door leaf against the bolt, then the electric bolt will start the low-power function to bring low temperature.
  - C: The Photoelectricity Control Technology, prevent the mechanical defect.

### Technical Specifications:

Place of Origin	Guangdong, China (Mainland)
Brand Name	PROYU
Model Number	PY-EL14
Fail Secure	Unlocked when energized
Face Plate	260Lx30Wx48H(mm)
Strike	100Lx25Wx3H(mm)
Bolt	16mmDIA, stainless steel 16mm throw
Voltage	DC12V
Start Current	950mA
Standby Current	150mA
Solid Bolt	Polishing housing, 2000Kg Holding Force
Suitable For	Wooden Door, Metal Door
Autolock Time Delay	0,3,6,9sec.
Signal Output	Lock status Output, NO/NC/COM
Surface Temp	Low Temperature
Induction Distance	8mm
Operating temp	-10~+55°C(14-131F)
Operating Humidity	0~90%(non-condensing)
Special Designed	Tested to 500000 operations
Face plate material	Stainless Steel
Weight	1.436kg

