

## Conventionele sirene Strobe voor brandmeldsysteem

- \* Compatibel met alle conventionele brandalarm bedieningspaneel
- \* Lange licht levensduur tot 40.000 flahsed
- \* Hoge geluidsniveau tot 100dB

|                            |   |
|----------------------------|---|
| Plaats van herkomst        | China (vasteland)   |
| Merknaam                   | Proyu   |
| Model Number               | PY-SG109  |
| Gebruik                    | Brand Alarm   |
| Afmeting                   | Length160mm, breedte 117mm, diepte 46mm                     |
| Gewicht                    | Netto gewicht 236g, Bruto Gewicht 285g                      |
| Temperatuur bij gebruik    | -10 ° C tot 50 ° C  |
| Relatieve luchtvochtigheid | 10% tot 93% relatieve vochtigheid, niet-condenserend        |
| Systeem (nominaal)         | 24 VDC (16V ~ 30VDC)  |
| Standby Actueel            | 60 uA @ 24VDC   |
| Alarm Actueel              | 100 tot 150 mA @ 24 VDC                                     |
| Strobe Flash Rate          | 1 flits per seconde   |
| Strobe Lifetime            | Minimum 40000 keer  |
| Alarm Sound Intensiteit    | Minimum 100dB   |
| Alarm Sound Tune           | Selecteerbaar I-Ambulance, II-Police Car, III Brandweerauto |





**ADDRESSABLE SOUNDER**  
Signal Loop: S1 – LOOP+, S2 – Loop-  
Power Loop: DC24V+, DC24- (24-28VDC input)  
Variable Sound Output: >90dB

Signal Loop Input  
S1 S2  
Power Loop Input  
(24V)

A terminal block with four gold-colored terminals. The first two terminals are labeled 'S1' and 'S2'. The last two terminals are labeled '(24V)'. A small green component is mounted between the second and third terminals.