

7 inch Video Door Phone With Time Attendance Function PY-V7D-K

Widely used for office, villa, home etc

Products Feature

- ◆Plastic camera, unlock by ID card, by password, by key, work attendance function, 25000 records, good design, CMOS or CCD sensor. 6 LED lights, night vision.
- ◆Handfree indoor monitor, 7 inch TFT, clear image.
- ◆Intercommunication, monitoring the outdoor, unlock.
- ◆Intercommunication is available between indoor and outdoor unit.
- ◆Brightness, chroma and ring adjustable.
- ◆3-chord melody rings for option.
- ◆Two cameras can be connected with four monitors. (different choice).
- ◆Four wires, DIY installation
- ◆Including in one kit: One indoor monitor, one outdoor camera, power adapter, user manual, cables.
- ◆Packing detail: Color box, 5 sets in one carton.
- ◆Surface mounting for monitor and camera
- ◆Monitor dimension: 230(L)×180(W)×18(H)mm
- ◆Camera dimension: 105(L)×165(W)×33(H)mm
- ◆Wiring requirements: 30M: RVV4 X 0.5 mm, 50M: RVV4 X 0.75 mm, 100M: RVV4 X 1.0 mm

Products Parameters:

- ◆Night vision illumination distance; more than 2 meters
- ◆Gain control: Automatic
- ◆Working temperature: -10°C-50°C
- ◆Illumination: 0.1 Lux
- ◆Camera angle: 92° wide-angle
- ◆Adapter input voltage: AC100-240V, 50Hz-60Hz
- ◆Adapter output voltage current: AC14.5V, 1200mA
- ◆Talk time delay: 90S
- ◆Monitor time delay: 30S
- ◆Dissipation: stand-by <0.5W, working <10W
- ◆Relative humidity: 10 %-90% (RH)