

4 **PY-V801ME11**

Parameters:

- 1. Camera: 1/4" CMOS
- 2. Min Illumination: 0.5Lux
- 3. Video: 1Vp-P / 75Ω
- 4. Adapter: AC100 ~ 240V, 50 / 60Hz
- 5. Adapter: DC15V / 1.2A
- 6. Installation: Wall Mount
- 7. Wires: 4-core (2 for ABS & amp; 2 for power)
- 8. Wires: 2-core (for power)
- 9. Operating Temperature: -20 ° C ~ 50 ° C

Parameters:

- 1. Camera: 1/4" CMOS
- 2. Min Illumination: 0.5Lux
- 3. Video: 1Vp-P / 75Ω
- 4. Adapter: AC100 ~ 240V, 50 / 60Hz
- 5. Adapter: DC15V / 1.2A
- 6. Installation: Wall Mount
- 7. Wires: 4-core (2 for ABS & amp; 2 for power)
- 8. Wires: 2-core (for power)
- 9. Operating Temperature: -20 ° C ~ 50 ° C

Specifications:

- 1. Screen: 7" TFT / LCD
- 2. Power Supply: AC100V-240V / 50-60Hz
- 3. Effective: 480 * 234 * 30
- 4. Power: ≤14W (max), ≤2W (standby)
- 5. Wiring: 4-core

Accessories:

- 1 * Camera (included)
- 1 * Monitor (Monitor)
- 1 * DC15V Adapter
- 1 * 5m 4-core Cable
- 1 * 2-core Cable
- 1 * Mounting Bracket