

RFID Digital Keypad PY-8831-JH



RFID Digital Keypad:

The keypad is compatible with MIFARE® 1K MIFARE® One-Card Pass cards. It is designed for use in access control systems. The keypad is powered by a 6.0V battery and has a maximum current consumption of 200mA. It is suitable for use in environments with a temperature range of 0°C to 70°C and a humidity of up to 80%.

RFID Digital Keypad Features:

1. Compatible with MIFARE® 1K MIFARE® One-Card Pass cards
2. Powered by a 6.0V battery with a maximum current consumption of 200mA
3. Suitable for use in environments with a temperature range of 0°C to 70°C and a humidity of up to 80%
4. Dimensions: 100mm x 50mm
5. Weight: 12g
6. Material: ABS
7. Color: Black
8. IP Rating: IP65
9. Operating Voltage: 6.0V

RFID Digital Keypad Specifications:

1. Operating Voltage: 6.0V (Battery Voltage: 4.5V - 6.0V)
2. Maximum Current Consumption: $< 100\mu A$
3. Maximum Power Consumption: $< 200mA$
4. Dimensions: 100mm x 50mm
5. Weight: 12g
6. Material: ABS
7. Color: Black
8. IP Rating: IP65

RFID Digital Keypad:



