

RF **PY-AC119**

RF

- 1.Enroll **RF**: **RF** & gt; **RF** & gt; **RF** enroll- & gt; enroll- **RF** & gt; **RF** .- & gt; **RF**
- 2.Enroll **RF**: **RF** & gt; **RF** & gt; **RF** enroll- & gt; **RF** (**RF**) enroll- & gt; enroll- **RF** & gt; **RF** .- & gt; **RF**
- 3.Set **RF**: **RF** & gt; Setting- & gt; **RF** & gt; **RF** & gt; 1-99 **RF**
- 4.Use **RF** SD **RF**: **RF** & gt; **RF** SD Card- & gt; SD **RF** & gt; ...
- 5.Manager **RF**: **RF** & gt; **RF** & gt; **RF** enroll- & gt; **RF** (**RF** / **RF**) enroll- & gt; enroll- **RF** & gt; **RF** .- & gt;
- 6.Delete **RF**: **RF** & gt; **RF** & gt; **RF** DATA- & gt; **RF** **RF** .- & gt; ...
- 7.Equipment: **RF** & gt; **RF** & gt; ...
- 8.Backup **RF**: **RF** & gt; **RF** & gt; **RF** enroll- & gt; **RF** (**RF** / **RF**) enroll- & gt; **RF** Esc **RF** enroll- & gt;

RF

| | |
|-----------|---|
| RF | 9200 |
| RF | 2000 |
| RF | 2000 |
| RF | RF Mini-SD / USB / RS485 |
| RF | 50000 |
| RF | 122 * 32PIX |
| RF | RF |
| RF | 0.7 RF |
| RF | 143 (L) * 80 (RF) * 42 (RF) RF |
| RF | 0.35KG |
| RF | DC12V |