

XX **F20** XXXXXXXXXXXXXXXXXXXXXXX

XXXXXXXXXXXXXXXXXXXX:

XXXX	F20
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	128 * 64
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	
XXXXXXXXXX	500DPI
XXXXXXXXXXXXXX	XXXXXXXXXXXXXXXXXXXX
FRR	& lt; = 0.1%
FAR	& lt; = 0.0001%
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	& lt; = 0.1 S
XXXXXXXXXXXXXXXXXXXX	XXXXXXXXXXXXXXXXXXXX
Real Time XXXXXXXXXXXXXXX	
XXXXXXXXXX	XXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXX	Off-line / XXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	
X	1: 1,1: XXXXXXX
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	XXXXXXXXXXXX / XXXX / XXXXXXX
XXXXXXXXXXXXXXXXXXXX	2000
XXXXXXXXXXXXXXXXXXXX	30,000 XXXXXXX
XXXXXXXXXXXX	TCP / IP, RS485
XXXXXX U XXXX / XXXXXXX	XXXXXXXXXXXXXXXXXXXX
XXXXX	XXXXXX
XXXXXXXXXXXXXXXXXXXX	XXXXXXXXXXXXXXXXXXXX
	XX
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	XXXXX
XXXXXX	Built-in XXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXX	XXXXXXXXXXXX / XXXXXXX
	XX
XXXXXXXXXXXXXXXXXXXX	XXXXXXXXXXXXXXXXXXXX
XXXXXXXXXXXXXXXXXXXX	XX
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	
XXXXXX	Wiegand 26 / Input / Output XXXXXXX
XXXXXXXXXX passback	XXXXXXXXXXXXXXXXXXXX
	XXXXXXXXXX, XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX, XXXXXXXXXXXXXXXXXXXXXXX
	XXXXXX
XXXXXXXXXXXXXXXXXXXX	XXXXX circumscribed, XXXXXXXXXXXXXXX
XXXXXX	DC 12V / 1A
	XXXXXXXXXXXXXXXXXXXXXXXXXXXX: 0degree-50degree XXXXXXX:
XXXXXXXXXXXXXXXXXXXXXXXXXXXX	80%
XXXXXXXXXXXXXXXXXXXX	181 (L) * 91 (XXXX) * 36 (X) XX
OEM	XXXX
SDK	XXXXXXXXXXXXXXXXXXXX

XXXXXXXXXXXXXXXXXXXX: XXXXXXXXXXXXXXXXXXXXXXX XXXXXXX, XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX